

Wall Light


An aesthetically pleasing designed, architectural spot / wall light luminaires. Lumitron's LMWL-34 is ideal for both outdoor and indoor applications such as walls, ceilings, corridors, building facades, walkways, especially for exclusive projects.

- Housing: corrosion resistant copper body with copper finish, or stainless steel or die cast aluminium with powder coating finish.
- Diffuser: heat-resistant, safety tempered glass lens.

- ☐ -AL: Aluminium body
- ☐ -ST: Stainless Steel
- ☐ -CP: Copper body
- Standards: IP65 Vandal resistant, dust-tight and water-jetproof. Conforming to DIN, VDE, IEC598-2-3, Class I Electrical.
- Stainless steel screws and silicone rubber gasket.
- Remote transformer for MR16 lamp.




LMWL-863



LUMITRON REF.	หลอด	มุมแสง	ขั้ว
LMWL-863-AL 7CFL PAR16	CFLPAR16 7W/220V	40°	GU10
LMWL-863-AL 50PAR16	PAR16 50W/220V	25°, 50°	GU10
LMWL-863-AL 35MR16	MR16 35W/12V	10°-40°	GX5.3
LMWL-863-AL 50MR16	MR16 50W/12V	10°-40°	GX5.3



LMWL-864



LUMITRON REF.	หลอด	มุมแสง	ขั้ว
LMWL-864-AL 7CFL PAR16	CFLPAR16 7W/220V	40°	GU10
LMWL-864-AL 50PAR16	PAR16 50W/220V	25°, 50°	GU10
LMWL-864-AL 35MR16	MR16 35W/12V	10°-40°	GX5.3
LMWL-864-AL 50MR16	MR16 50W/12V	10°-40°	GX5.3