LMDL - 139

Recessed Adjustable Downlight

Applications

 A range of aesthetically-pleasing design, wall washer recessed downlight, vertical lamp direction. Lumitron's LMDL-139, suitable for PAR38 lamp 70-120W, to provide sufficient light output where low to medium ceiling height installation is required. Ideal for commercial lighting applications, exhibition halls, exclusive residential projects, shopping arcades, hotels, condominiums, and etc.

Specifications

- Suitable for PAR38 120W, halogen PAR38: 100W.
- Low brightness with good shielding of lamp position.
- Reflector: high purity, mirror anodized aluminium chemically brighten. Available in various choices of finish. Standard offer is SM: mirror anodized reflector.

□ SM: mirror anodized aluminium reflector


☐ GM: Gold mirror reflector

- Housing: steel with black polyester powder coated for superior corrosion resistance.
- Trim: white finish as standard, black color on request.
- · Lampholders: E27 base, ceramic type.
- Lamp adjustable aiming and orientation in both vertical 0°-358° and vertical 0°-35°.
- Mounting: recessed mounting by employing supporting tools and locking devices.
- · Cut-out diameter 182mm.









N

LUMITRON REF.	Lamp	Beam Angle	Base
LMDL-139-120PAR38	PAR38 120W	12°, 30°	E27
LMDL-139-100HALPAR 38	HAL-PAR38 100W	10°, 30°	E27

www.lumitronlighting.com 58