


## LMTL - 59

### MR 16 - Halogen Track Light / Spot Light

A mini track / spot light luminaires for indoor use, employs low voltage halogen lamp MR16. Lumitron's LMTL-59, is suitable for decorative interiors, display windows, shops, showrooms, exhibition halls, department stores, and other commercial areas.

#### Specifications

- Housing: corrosion resistant die cast aluminium body with polyester powder coating finish in white, black, or silver color. Other color available on request.
- ☐ -WH: white color
- ☐ -BK: black color
- ☐ -SV: silver color
- Transformer: built-in type, accommodates 220Vac / 12Vac transformer.
- Lamp beam angle 10°, 20°, 30°, and 40°. Recheck lamp specifications.
- Suitable for 12V MR16 20W up to 50W.
- Lampholder: GX5.3, ceramic type, VDE approved.
- Standards and Conformities: DIN, VDE, IEC, Class I Electrical.
- Installation/Mounting: track or surface mounting.



MR16 12V	10°	MR16 12V	24°
7500 lx	1,0 m	10950 lx	0,5 m
1875 lx	2,0 m	2850 lx	1,0 m
835 lx	3,0 m	710 lx	2,0 m
470 lx	4,0 m	315 lx	3,0 m
E <sub>max</sub> (lux) H		E <sub>max</sub> (lux) H	
MR16 12V	38°	MR16 12V	60°
5500 lx	0,5 m	2750 lx	0,5 m
1425 lx	1,0 m	715 lx	1,0 m
355 lx	2,0 m	180 lx	2,0 m
160 lx	3,0 m	80 lx	3,0 m
E <sub>max</sub> (lux) H		E <sub>max</sub> (lux) H	

#### Ordering Information

Lumitron Ref.	Lamp Type	Beam Angle	Color Temp.	Base	Remark
LMTL-59-20MR16	MR16 20W	10°-40°	3,000°K	GX5.3	
LMTL-59-35MR16	MR16 35W	10°-40°	3,000°K	GX5.3	
LMTL-59-50MR16	MR16 50W	10°-40°	3,000°K	GX5.3	