




LMTL - 99

70-150W High Power Spot Light

A compact discharge track / spot light luminaires for indoor use, employs powerful metal halide light source. Lumitron's LMTL-99, is suitable for decorative interiors, display windows, shops, showrooms, exhibition halls, department stores, and other commercial areas where require high illumination.

Specifications

- Housing: corrosion resistant metal with polyester powder coating finish in white or black color.
- ☐ -WH: white color
- ☐ -BK: black color
- Reflector: high purity anodized aluminium reflector chemically brighten.
- Lens Assembly: thermal shock resistant safety glass in frame.
- Control Gear: built-in type, accommodates ballast, ignitor, capacitor and lampholders VDE approved.
- Lampholder: RX7S for MH-DE lamp.
- Lumitron offers only anti-cycling ignitor, super-imposed version to avoid ballast failures during ends of lamp life.
- Standards and Conformities: DIN, VDE, IEC, Class I Electrical.
- Installation/Mounting:
 - ☐ -SM: surface mounting version
 - ☐ -TR1: 1-phase track mounting version
 - ☐ -TR3: 3-phase track mounting version



Ordering Information

Lumitron Ref.	Lamp Type	Lumens	Color Temp (K)	Base	Remark
LMTL-99-70MH-DE	MH-DE 70W	5,500	3,000-4,200	RX7s	
LMTL-99-150MH-DE	MH-DE 150W	11,250	3,000-4,200	RX7s	