





Wall Surface Mounted Down Light - IP 54


Architectural wall luminaries, Lumitron's LMWL-7, is specifically designed for decorative amenity applications such as public areas, commercial and residential areas. Applicable for various types of light source, including compact fluorescent lamps for energy saving applications. Ideal for terraces, corridors, walkways, columns, trees, entrances, and facades.


Specifications

- Corrosion resistant, die cast aluminium body.
- Colour: UV resistant polyester powder coat finish in White RAL 9010, Black RAL 9005, or silver aluminium color.
- Diffuser: high impact, UV-stabilized polycarbonate lens with choices:
 - ☐ CL: clear polycarbonate diffuser with louver.
 - ☐ OP: opal polycarbonate diffuser.
- Stainless steel screws.
- Durable silicone rubber gasket.
- Lampholder: VDE approved E27, G24d-3.
- Built-in control gear.
- IP54 Dust proof and splash proof conforming to DIN, VDE, IEC, Class I Electrical.









Ordering Information

Lumitron Ref.	Lamp Type	Lumen	Color Temp.	Base	Remarks
LMWL-7-60GLS	GLS 60W	730	2,700K	E27	Recheck lumen with lamp
LMWL-7-26PLC	PLC 26W	1,800	2,700-4,000K	G24d-3	catalog.
LMWL-7-70HPS	HPS 70W	5,600	2,000K	E27	
LMWL-7-70MH	MH 70W	5,300	3,200-4,000K	E27	