



## **LMRW - 16**


## Street Light / Area light - IP 65

An extinctive designed range of premium street lantern offering efficient lighting for safe and comfortable driving. Lumitron's LMPT-16, is designed to accept wide range of discharge lamps. Thanks to its unique shape and form. It provides elegant appearance, aesthetically suitable for prestigious projects. Ideal for major traffic roads, residential streets, arenas, modern architectural environments.

## **Specifications**

- Housing: sturdy construction, one-piece die cast aluminium alloy.
- Finish: polyester powder coated for superior corrosion resistance in black, grey, or white. Other color available on request.
- Reflector: multi faceted anodized aluminium reflector. Provides wide beam light distribution.
- Diffuser: heat resistant, safety glass lens.
- Stainless steel screws and non-aging durable silicone rubber gasket.
- Lampholder: porcelain E27 or E40, 5 KV pulse rating.
- Control Gear: Lumitron fixtures are standard with P.F corrected system. Lumitron employs only super-imposed ignitor (where required) to avoid ballast failures during ends of lamp life.
- IP 65, dustproof and jet-proof. Class I Electrical.
- Standard and Conformities: DIN, VDE, IEC 598-2-3-1993.
- Custom design decorative pole. Please contact Lumitron for more information.





## **Ordering Information**

Lumitron Ref.	Lamp Type	Lumens	CCT. (K)	Base	Remark
LMRW-16-250MV	MV 250W	13,000	4,000	E40	Recheck lumen with lamp catalog.
LMRW-16-400MV	MV 400W	22,000	4,000	E40	
LMRW-16-150HPS	HPS 150W	14,500	2,000	E40	
LMRW-16-250HPS	HPS 250W	27,000	2,000	E40	
LMRW-16-400HPS	HPS 400W	48,000	2,000	E40	
LMRW-16-150MH	MH 150W	14,250	3,200-4,000	E27	
LMRW-16-250MH	MH 250W	21,000	4,000-6,000	E40	
LMRW-16-400MH	MH 400W	36,000	4,000-6,000	E40	