

# LED Floodlight - IP65




Die Cast Aluminium Body	Safety Tempered Glass	CRI >80	100-240 VAC	≥0.95 Power Factor
-------------------------	-----------------------	---------	-------------	--------------------

**IP65**




Warm White Cool White Daylight




## ITFL-76

REF.	วัตต์	ลูเมน	ใช้แทน
ITFL-76-50W	50W	4,150-4,500	MV 250W, MH-HPS 100-150W
ITFL-76-80W	80W	6,640-7,200	MV 400W, MH-HPS 150W-250W
ITFL-76-100W	100W	8,300-9,000	MV 400W, MH-HPS 150W-250W




## ITFL-68

REF.	วัตต์	ลูเมน	ใช้แทน
ITFL-68-100W	100W	8,300-9,000	MV 400W, MH-HPS 150W-250W
ITFL-68-120W	120W	9,960-10,800	MV 400W, MH-HPS 250W
ITFL-68-160W	160W	13,280-14,400	MV 400W, MH-HPS 250W-400W
ITFL-68-200W	200W	16,600-18,000	MV 400W, MH-HPS 250W-400W



## ITFL-78

REF.	วัตต์	ลูเมน	ใช้แทน
ITFL-78-150W	150W	12,450-13,500	MV 400W, MH-HPS 250W-400W
ITFL-78-180W	180W	14,940-16,200	MV 400W, MH-HPS 250W-400W



## ITFL-80

REF.	วัตต์	ลูเมน	ใช้แทน
ITFL-80-200W	200W	16,600-18,000	MV 400W, MH-HPS 250W-400W
ITFL-80-240W	240W	19,920-21,600	MH-HPS 400W